



Long life. Less energy. Better lighting

The 3000 LEDlights Hood is your bright new friend in the kitchen. Using far less energy than other lights, with a much longer life expectancy, it provides expert illumination for greater detail while cooking.

Product Benefits & Features

LEDlights for more refined cooking

Our LEDlights use far less energy than other lights, with a much longer life expectancy. And they provide expert illumination for greater detail while cooking.



- Installation type: Traditional, width 60 cm
- Recirculatory intensive: 85 m³/h
- Power settings in recirculation mode (high/low): 81 / 65 m³/h
- Electronic push buttons control with 3+Intensive speeds
- Backlight controls
- Electronic Regulation
- Number of speeds: 3+Intensive
- Light Temperature, K
- Watt Volt
- Grease filter type and number: Aluminium Cassette, 2
- Indicator for grease filter saturation
- Indicator for carbon filter saturation
- Automatic switch off for intensive mode
- Maximum noise level (high/low): / dB(A)

A cooker hood you can rely on

Clean kitchen air with this efficient cooker hood. Its reliable motor helps to efficiently reduce and remove any odours resulting from cooking.

Capably capturing kitchen fumes

Reliably capturing cooking odours and fats, this long-lasting filter can be simply replaced when necessary.

Hood Settings. On Demand. With Electronic Controls

Innovative Electronic Controls make regulating the cooker hood functions more convenient. From modifying the fan speed to adjusting the light settings, take complete control of the cooking process.

Product Specification

Product Number Code	942 150 822	Sound power max speed, dB(A)	63
EAN	7332543619375	Sound power min speed, dB(A)	53
EPRELRegCode	85284	Recirculation Intensive, m³/h	85
Annual Energy consumption, KWh/annum	64.5	Recirculation Max, m³/h	81
Energy Efficiency class	D	Recirculation Min, m³/h	65
Fluid dynamic efficiency class	E	Recirc. sound power max, dB(A)	68
Fluid dynamic efficiency index	8.1	Recirc. sound power min, dB(A)	64
Lighting efficiency class	A	LightTemperature	3000
Lighting efficiency index	76.1	Minimum distance from cooking top ELECTRIC	50
Grease filter efficiency class	E	Minimum distance from cooking top GAS	65
Grease filter efficiency index	56	Weight gross cleaner and accessories with packaging	6.2
Height total	132.3	Weight net cleaner and accessories no packaging	5
Height max. external	132.3	Package heigth	563
Width mm	599	Package width	647
Depth mm	512.5	Package depth	178
Air outlet	125	Weight package Corrugated Cardboard	1070
Main colour	Stainless Steel	Weight package PE	15
Charcoal filter type	MCFE06	Weight package Polystyrene (EPS/EPP)	100
Charcoal filter PNC	902 980 050	Country of origin	IT
Voltage	220-240		
Capacity intensive, m³/h	270		
Capacity, Max m³/h	190		
Capacity, Min m³/h	110		
Sound power intensive, dB(A)	71		

PSGBCH160D363001

