

FEE53600ZM





Customised Cycles, Complete Cleaning

Advanced sensors in AEG dishwashers automatically adjust the time, temperature and water usage according to the soil level of each load. So you can have customised cycles for each clean with the very best results every time.

Product Benefits & Features



Dedicated protection for your delicate glasses

Glasses are often the most delicate items in your dishwasher, which means they need special care. The upper basket in this dishwasher has soft rubber spikes to support and protect glasses. The SoftSpikes stabilise your glasses and mugs efficiently, preventing them from falling over and possibly





Make the most of the time you have available with the programme time that suits and enjoy the convenience

- Ready when you are
- delay start function in our dishwashers. Preset a of having clean dishes when you want them.
- Open-door drying with AirDry



AirDry technology delivers up to three times better drying performance when compared to closed-door systems. The door automatically opens at the end of the drying phase and air is circulated inside the machine. Dishes emerge perfectly dry. Every time.

- · SENSORLOGIC dishwasher
- · Water sensor detects the level of dirt and adjusts water consumption
- · LED display
- AutoOff
- Warm water 60°C
- 5 programmes, 4 temperatures
- Dishwasher programmes: 30 MIN 60°, AutoSense 45°-70°, Eco, Glass 45°, Intensive 70°
- Options:Time Saver, XtraDry
- Delay start option from 1 to 24 hours
- Remaining time
- Inverter motor
- · Height adjustable upper basket, even when fully loaded
- Upper basket with 2 Red softspikes, Plastic coloured handle
- · Cutlery basket
- · Lower basket with 2 foldable plate racks, Plastic coloured handle
- AQUA-CONTROL
- · Installation in height
- · Anti fingerprint stainless steel finishing
- Panel with symbols
- · Indications for salt and rinse aid



FEE53600ZM

Product Specification	
Product Number Code	911 524 061
Bar code	7332543520824
EnergyClassE20	D
EnergyCons100CycleE20	84
RatedCapacityE20	13
WaterConsE20	9.9
ProgrammeDurE20	3:57
NoiseClassE20	В
NoisedBAE20	44
OffModePwE20	0.5
StandByPwE20	0.5
DelayStartE20	4
Installation in height	Yes
Installation	I
Inlet hose type of	Aqua control
Anti-flood device	Floating switch
Water supply	Cold or hot
Panel colour	Stainless steel
Required fuse (A)	10
Connected load (W)	1950
Voltage	220-240
Cord length external	1.5
Height total	818
Width mm	596
Depth mm	575

Built in depth mm	550
Built in height (min), mm	820
Built in width mm	600
Weight gross cleaner and accessories with packaging	41.82
Weight net cleaner and accessories no packaging	40.3
Package heigth	864
Package width	635
Package depth	680

