



Up to 3x better coverage without using extra water

Even closely stacked or larger dishes get thoroughly cleaned in the 6000 SatelliteClean® Dishwasher. The innovative spray arm provides up to 3x better spray coverage, guaranteeing corner-to-corner cleaning.

Product Benefits & Features

SatelliteClean®. Powerful dishwashing. Without using extra water

Even closely stacked or larger dishes receive deep cleaning with SatelliteClean®. The innovative spray arm guarantees corner-to-corner cleaning. With up to 3x better spray coverage providing stunning results across every surface.



Superior Cleaning and best glass care

Your delicate glasses can not be cleaned in a safer way thanks to AEG SoftGrip and SoftSpikes which perfectly holds your glasses, protecting them from getting damaged.



Customisable eco dishwashing with just a touch

With the 6000 QuickSelect Dishwasher you can use the My Time slider to select the cycle time, the Ecometer will display the eco performance for each of the possible selections. So, you can easily select the best option with just a touch.



- 44dB - ExtraSilent 42dB
- Sensorlogic Dishwasher in AutoSense program
- Water sensor detects the level of dirt and adjusts water consumption
- LED Display with QuickSelect
- Touch control for programs and functions selection
- AutoOff
- Warm water 60°C
- 7 programmes, 4 temperatures
- Dishwasher programmes: 160 Minutes, 60 Minutes, 90 Minutes, AUTO Sense, Eco, Machine Care, Quick 30 Minutes
- Options:Extra Silent, GlassCare, XtraPower
- Ceiling shower
- ProWater system with extra ceiling spraying arm
- ProClean Satellite Spray arm
- Delay start option from 1 to 24 hours
- Remaining time
- SpotControl with 2 colours
- Buzzer
- Inverter motor
- XXL tub
- Sliding door 670-825 mm
- Height adjustable upper basket, even when fully loaded
- Upper basket with 2 Foldable racks, 2 Foldable wires for glasses, 2 Soft Spikes, 6 wine glass soft grips, Plastic handle AEG
- Cutlery drawer with knife support
- Lower basket with 4 foldable plate racks, Plastic handle
- AQUA-CONTROL
- Installation in height
- GlassProtectionSystem
- Indications for salt and rinse aid

Open the door to dry dishes

AirDry delivers up to 3x better drying performance when compared to closed-door systems. The door automatically opens at the end of the drying phase and air is circulated inside the machine. Dishes emerge perfectly dry. Every time.

At-a-glance check

This dishwasher has a clever way to keep you fully up to date with the status of your dishes. Its beam-on-floor technology projects a red light onto the floor while the cycle is still in progress. And when everything is ready to unload, it switches to a green one. Simple, and effective.

Product Specification

| | | | |
|------------------------|--|---|-------|
| Product Number Code | 911 434 552 | Cord length external | 1.6 |
| EPRELRegCodeE20 | 336221 | Height total | 818 |
| Bar code | 7332543671939 | Width mm | 596 |
| EnergyClassE20 | D | Depth mm | 550 |
| EnergyCons100CycleE20 | 86 | Built in depth mm | 570 |
| RatedCapacityE20 | 15 | Built in height (min), mm | 820 |
| WaterConsE20 | 11 | Built in width mm | 600 |
| ProgrammeDurE20 | 4:00 | Weight gross cleaner and accessories with packaging | 40.1 |
| NoiseClassE20 | B | Weight net cleaner and accessories no packaging | 38.39 |
| NoisedBAE20 | 44 | Package height | 870 |
| OffModePwE20 | 0.5 | Package width | 635 |
| StandByPwE20 | 0.5 | Package depth | 680 |
| Installation in height | Yes | Weight package Corrugated Cardboard | 120 |
| Installation | FI | Weight package Paper/Carton | 10.5 |
| Inlet hose type of | Aqua control | Weight package Wood | 300 |
| Anti-flood device | Floating switch | Weight package PE | 281 |
| Water supply | Cold or hot | Weight package PP | 40 |
| DelayStartE20 | 4 | Weight package Polystyrene (EPS/EPP) | 957 |
| Dishwasher programs | 160 Minutes, 60 Minutes, 90 Minutes, AUTO Sense, Eco, Machine Care, Quick 30 Minutes | Weight package Rubber | 2 |
| Panel colour | Black | Country of origin | IT |
| Required fuse (A) | 10 | | |
| Connected load (W) | 1950 | | |
| Voltage | 220-240 | | |

