

CCE84751CB







Your kitchen, your way.

Get the Kitchen Design Freedom you need. This duo combines an induction hob with a powerful integrated extractor, so you don't have to worry about a hob and separate hood. Now you can plan your kitchen layout with the freedom your creativity needs.

Product Benefits & Features



Get the Kitchen Design Freedom to plan your kitchen your way

This combination of an induction hob with a powerful integrated extractor gives you the Kitchen Design Freedom you need. Now you have more space for your versatile kitchen layout ideas.

- Bridge XT: 2 in 1 Hob-Hood-Combination Recirculation
- Features Hob
- Hob²Hood function
- 4 Induction cooking zones
- Direct Control sliding touch control
- Pause-Funktion
- Timer
- Child-lock
- Automatic switch off
- Build in type: Integrated or on top
- Features Hood
- Inverter motor
- 9 speeds
- Recirculatory
- · Indicator for grease filter saturation



Combine cooking zones for bigger pots and pans. Double Bridge

Got a large pot for a casserole? Using a plancha? Well with Double Bridge, you can combine two cooking zones on both sides of the hob to give uniform heat distribution to your large pots and pans.



After cooking, quietly clear the kitchen air with Breeze

After the cooking is done you want to be able to enjoy your meal and discreetly freshen the kitchen air. The Breeze function quietly clears the kitchen air, without disturbing the ambiance for you and your guest.

Easy to clean. Easy to remove. 2-in-1 Filter

The 2-in-1 Filter combines both a charcoal and grease filter that removes odours and grease. If the appliance is installed in recirculation mode, then a 2-in-1 filter is needed. The Filter is easy to remove and can be washed in the dishwasher.

Automated extraction. With Hob2Hood

Hob2Hood technology allows for automated extraction during cooking. If you turn the temperature up or down on the hob, the extractor's fan will adjust itself accordingly. Meaning all your focus goes into your food.



AEG CCE84751CB ComboHob Width Induction Auto function Bridge Recirculatory

CCE84751CB

Product Specification			
Product Number Code	949 597 950	Left Rear - Power, W / Diam., mm	2300/3200W/210mm
EPRELRegCode	1104666	Right Front - Power, W / Diam., mm	2300/3200W/210mm
Bar code	7332543838639	Right Rear - Power, W / Diam., mm	2300/3200W/210mm
Annual Energy consumption, KWh/annum	28.8	Built in height mm	212
Energy Efficiency class	A+	Width mm	830 515
Fluid dynamic efficiency class	Α	Depth mm	780
Fluid dynamic efficiency index	32.4	Width cutting	490
Grease filter efficiency class	В	Depth cutting	
Grease filter efficiency index	85.1	Cord length external	1.5
Capacity, Min m³/h	270	Total electricity loading	7350
Capacity, Max m³/h	500	Voltage	220-240V/400V2N
Capacity intensive, m³/h	630	Weight gross cleaner and accessories with packaging	27.02
Sound power min speed, dB(A)	49	Weight net cleaner and accessories	21.22
Sound power max speed, dB(A)	64	no packaging	
Sound power intensive, dB(A)	70	Package heigth	540
Recirculation Min, m³/h	250	Package width	935
Recirculation Max, m³/h	465	Package depth	619
Recirculation Intensive, m³/h	585	Weight package Corrugated Cardboard	8200
Recirc. sound power min, dB(A)	54	Weight package Paper/Carton	0
Recirc. sound power max, dB(A)	70	Weight package Wood	0
Off mode power,W	0.49	Weight package PE	40
Hob type	Induction ExtractorHob	Weight package PP	0
Main colour	Black	3 1 3	-
Left Front - Power, W / Diam., mm,	2300/3200W/210mm		

PSGBHO210DE00009 PSGBHO210DE0000B



