


IKE85441XB





Combine two zones to cook more

The 6000 Bridge Induction Hob can easily cope when you're cooking with bigger pans. The Bridge button links two cooking zones together to fit any large or long pan. The bridged zone will share the same temperature and time settina.

Product Benefits & Features



Combine 2 cooking zones with Bridge

The Bridge function combines two cooking zones together to fit any large or long pan. Sharing the same temperature and time setting, the linked zones are ideal when you're cooking for dinner parties or bigger celebrations.

Whether using small or large cookware, this specialised

XL Triple zone delivers even heat that correlates to the

size of the pot or pan being used. It can be used for pot

Sized for superior taste with XL Triple Zone

- · Independent hob with controls Number cooking zones
- Hob type: Induction
- New XL frame concept OptiFit Frame™
- Hob²Hood
- · Induction zones with power booster function
- Pause function for short interruptions
- · Illuminated controls
- Automatic fast heating up
- Pot detection
- Eco Timer
- · Count up timer
- Timer function
- OptiHeat Control
- · Acoustic signal with switch off option
- · Child safety lock function
- Key-lock function
- · Hob safety: Automatic Switch Off
- OptiFix™: extremely fast installation concept
- SlimFit
- · Ceramic glass colour: Black

Less steps and more control with Direct Touch Controls

The Direct Touch Controls user interface uses intuitive numbers 1-9 so you can set the right temperature right away without having to toggle through the plus and minus buttons.

sizes from 125mm to 320 mm.

Quicker heat for extra speed with PowerBoost

No more waiting around for pots to boil. The PowerBoost function gives you an instant burst of heat, boiling water in under 90 seconds. It's perfect for tasks like boiling a large pot of water quickly.

Hob timer. Built for precision

The built in hob timer can be set up to one hour, and will automatically power the hob down when it elapses. For effortlessly precise results.



IKE85441XB

Installation Independent Product Number Code 949 597 270 Weight package Corrugated Cardboard Weight package Paper/Carton Weight package Paper/Carton Weight package Paper/Carton Weight package Paper/Carton Weight package Wood Weight package PE Weight package PE Weight package PE Weight package PP Weight package PP Weight package PP Weight package PP Weight package PO Weight package Rubber Type of plug No Country of origin	
Product Number Code EAN 7332543564613 Built in height mm 46 Weight package Paper/Carton Weight package Wood Weight package PE Weight package PE Weight package PP Weight package PO Weight package PU Weight package PU Weight package PU Weight package Rubber Type of plug No Country of origin	
EAN 7332543564613 Cardboard Built in height mm 46 Weight package Paper/Carton Width mm 766 Weight package Wood Depth mm 516 Weight package PE Width cutting 750 Weight package PP Depth cutting 490 (EPS/EPP) Frame Colour - colour of the frame Stainless steel Weight package PU Hob type Induction Full Weight package Iron Cord length external 1.5 Weight package Rubber Type of plug No Country of origin	600
Built in height mm 46 Weight package Paper/Carton Weight package Wood Weight package PE Weight package PE Weight package PE Weight package PP Weight package PU Weight package PI Cord length external 1.5 Weight package Rubber Type of plug No Country of origin	640
Width mm 766 Depth mm 516 Weight package PE Weight package PP Weight package POlystyrene (EPS/EPP) Frame Colour - colour of the frame Stainless steel Hob type Induction Full Weight package PU Weight package PU Weight package PU Weight package PU Weight package Rubber Type of plug No Country of origin	
Depth mm 516 Weight package PE Weight package PP Weight package PP Weight package PP Weight package Polystyrene (EPS/EPP) Frame Colour - colour of the frame Stainless steel Weight package Polystyrene (EPS/EPP) Weight package PU Weight package PU Weight package PU Weight package Iron Weight package Iron Cord length external 1.5 Weight package Rubber Type of plug No Country of origin	0
Weight package PP Weight package PP Weight package Polystyrene (EPS/EPP) Frame Colour - colour of the frame Hob type Induction Full Veight package PU Weight package Rubber Type of plug No Country of origin Total electricity loading	
Depth cutting Depth cutting 490 (EPS/EPP) Frame Colour - colour of the frame Hob type Induction Full Cord length external Type of plug Total electricity loading Weight package Polystyrene (EPS/EPP) Weight package PU Weight package Iron Weight package Rubber Country of origin	0
Frame Colour - colour of the frame Hob type Induction Full Cord length external Type of plug Total electricity loading Stainless steel Weight package PU Weight package Iron Weight package Rubber Country of origin	5
Frame Colour - colour of the frame Hob type Cord length external Type of plug Total electricity loading Stainless steel Hoeight package PU Weight package Iron Weight package Rubber Country of origin	308
Cord length external 1.5 Weight package Rubber Type of plug No Country of origin Total electricity loading 7350	0
Type of plug No Country of origin Total electricity loading 7350	0
Total electricity loading 7350	0
, ,	DE
1 of front Down /Diameter 2200/2200/N/240	
Left front - Power/Diameter 2300/3200W/210mm	
Rear - Power/Diameter 2300/3200W/210mm	
Middle front - Power/Diameter 2300/3200W/210mm	
Right front - Power/Diameter 1400/2500W/145mm	
Right rear - Power/Diameter 1800/2800W/180mm	
Voltage 220-240/400V2N	
Weight gross cleaner and accessories with packaging 13.36	
Weight net cleaner and accessories no packaging 12.34	
Package heigth 118	
Package width 868	

