

**Keep your kitchen smelling fresh and clean**

Simply designed to suit any kitchen, this effective hood whips away cooking odours to keep your kitchen smelling fresh.

---

**Product Benefits & Features****Ensures your kitchen will always smell nice and fresh!**

Three speed levels give you exactly the amount of air power you need, from high when frying, to low when you just want to refresh the kitchen air.

- Installation type: Chimney, width 60 cm
- Power settings in recirculation mode (high/low): 415 / 250 m<sup>3</sup>/h
- Push button controls with 3 speeds
- Number of speeds: 3
- Light Temperature, K
- Watt Volt
- Grease filter type and number: Aluminium mesh, 2
- Maximum noise level (high/low): 71/51 dB(A)

**Why spend more time cleaning appliances than you have to?**

The aluminium cassette filter in this cooker hood is definitely low-maintenance. When it needs to be cleaned, simply pop it in the dishwasher!

**Product Specification**

Product Number Code	942 022 033	Sound power min speed, dB(A)	51
EAN	7332543610808	Recirculation Max, m <sup>3</sup> /h	415
EPRELRegCode	50449	Recirculation Min, m <sup>3</sup> /h	250
Annual Energy consumption, KWh/annum	96.4	Recirc. sound power max, dB(A)	73
Energy Efficiency class	C	Recirc. sound power min, dB(A)	62
Fluid dynamic efficiency class	D	LightTemperature	3000
Fluid dynamic efficiency index	15.3	Minimum distance from cooking top ELECTRIC	50
Lighting efficiency class	A	Minimum distance from cooking top GAS	65
Lighting efficiency index	46	Weight gross cleaner and accessories with packaging	14.2
Grease filter efficiency class	C	Weight net cleaner and accessories no packaging	11.5
Grease filter efficiency index	75.1	Package heighth	625
Height total	678	Package width	700
Height max. external	1180	Package depth	460
Width mm	598	Weight package Corrugated Cardboard	2105
Depth mm	450	Weight package PE	64
Air outlet	150	Weight package Polystyrene (EPS/EPP)	439
Main colour	Stainless Steel	Country of origin	PL
Charcoal filter type	ECFB01		
Charcoal filter PNC	902 979 876		
Voltage	220-240		
Capacity, Max m <sup>3</sup> /h	600		
Capacity, Min m <sup>3</sup> /h	295		
Recirculation High	330		
Sound power max speed, dB(A)	68		

